

SPECIFICATION SHEETS



PRODUCT NAME:	Inferno-Lite® ICGCP916WW
PRODUCT CODE:	ICGCP916WW
PERFORMANCE TESTING:	Fire Rating: UL Labeled for 3/4 hour in 1 hour rated masonry and door openings. UL File# KCMZ.R13833 Attack Resistance: H.P. White Level 1- TP - 0500.02
CONSTRUCTION:	114" Wire Glass .050" Urethane 114" Polycarbonate .050" Urethane 114" Wire Glass
THICKNESS:	13116" Nominal (.870")
THICKNESS TOLERANCE:	.792" / .950"
WEIGHT:	9.94 Lbs. Square Foot
MAXIMUM SIZE:	1156 square inches of clear opening Maximum width and height dimension of exposed glazing is 34".
APPLICABLE STANDARDS:	ANSI Z97.1 ASTM C 1349 CPSC 16 CFR 1201 (Category I and II) UL9 ASTM C 1036
SINGLE RESPONSIBILITY:	Global Security Glazing products are covered by our Single Responsibility® Program that ensures one firm has handled and is accountable for all phases of manufacturing.
INSTALLATION:	All glazing to be installed with ULclassified Metacaulk 950 or Blazeseal joint treatment as manufactured by Metalines, Inc. to maintain UL label requirements. For general glazing guidelines refer to the Glass Association of North America (GANA) Glazing Manual 2004 or latest edition. Contact Global Security Glazing for publication GSG-23-03 "Glazing Guidelines" for further information. Note: ICGCP916WW is manufactured with two plies of wire glass which are impossible to align perfectly. Visibility may be obscured to some degree. ICGCP916WW is only available in clear glazing.