

SPECIFICATION SHEETS



PRODUCT NAME:	Lexgard[®] MPC 375
PRODUCT CODE:	MPC 375
PERFORMANCE TESTING:	Forced Entry: ASTM F1 233 Class III ASTM 1915 Grade 3 HP White Level II-TP-0500.02 WMFL Level III
CONSTRUCTION:	This product is laminated polycarbonate and contains exposed polycarbonate surfaces with abrasion resistant coatings on both sides.
THICKNESS:	3/8" Nominal (.369")
THICKNESS TOLERANCE:	.332" / .406"
WEIGHT:	2.29 Lbs. / Square Foot
MAXIMUM SIZE:	72" x 96"
OPTIONS:	Translucent white interlayer
TECHNICAL DATA:	U-Value .84 Shading Co-efficient .92 Light Transmission .77
SINGLE RESPONSIBILITY:	Global Security Glazing products are covered by our Single Responsibility [®] Program that ensures one firm has handled and is accountable for all phases of manufacturing.
INSTALLATION:	All glazing should be installed in accordance with the guidelines set forth in the current edition of the Glass Association of North America (GANA) Glazing and Sealant Manuals. Glazing systems should incorporate a weep system to allow moisture and water to escape the glazing channel. Recommended Clearance: Face: 1/8" per side Edge: 1/4" Bite: 1"