

SPECIFICATION SHEETS



PRODUCT NAME:	Secur-Tem® 3	
PRODUCT CODE:	SM3	
PERFORMANCE TESTING:	<p>Secur-Tem® products are chemically or heat strengthened all glass laminates designed to protect against physical attack.</p> <p>Testing: By Froehling & Robertson Incorporated and Wiss, Janney, Elstner Associates, Inc. Meets approximately 10-15 minutes of physical attack.</p>	
CONSTRUCTION:	*Product construction is proprietary.	
THICKNESS:	9/16" Nominal (.554")	
THICKNESS TOLERANCE:	.507" / .600"	
WEIGHT:	5.938 Lbs. / Square Foot	
MAXIMUM SIZE:	60" x 96"	
OPTIONS:	Tinted glass, tinted interlayer, transparent mirror, reflective glass, wire glass, Low E glass, insulated units. (The use of some options may alter product thickness)	
TECHNICAL DATA:	<p>U-Value .89</p> <p>Solar Heat Gain Co-efficient .71</p> <p>Light Transmission .86</p>	
APPLICABLE STANDARDS:	ANSI Z97.1 CPSC 16 CFR 1201 (Category I and II) ASTM C 1036	ASTM C 1172 ASTM C 1048 ASTM C 1422
SINGLE RESPONSIBILITY:	Global Security Glazing products are covered by our Single Responsibility® Program that ensures one firm has handled and is accountable for all phases of manufacturing.	
INSTALLATION:	<p>All glass should be installed in accordance with the guidelines set forth in the current edition of the Glass Association of North America (GANA) Glazing and Sealant Manuals. Glazing systems should incorporate a weep system to allow moisture and water to escape the glazing channel.</p> <p>Recommended Clearance: Face: 1/8" per side Edge: 1/4" Bite: 3/4"</p>	